

SUPPORTING LIFE 24x7 Available Range: 63kVA - 200kVA



### SUPPORTING YOUR POWER NEEDS

JCB

JCB Power Products offer an extensive range of high specification diesel generators to meet the customers' requirements for any power application globally. Each JCB generator is designed to the highest specification to deliver outstanding reliability, class-leading performance and increased efficiency.

JCB Generators offer power solutions ranging from 8 kVA to 3300 kVA, meeting all requirements globally.

Backed by finest product support team for the entire product range, JCB Generators are trusted across the world to deliver power applications. The comprehensive range of generators provide support to residential properties, hospitals, offices, educational institutions, hotels & restaurants, commercial & agricultural sector, food industry and many more.



#### 125 kVA Generator



#### **Fuel Efficient**

- Lowest cost per hour
- Save more than ₹2,75,000<sup>\*</sup> with JCB 125 kVA on 5000 hours running
- Save over ₹1,65,000<sup>\*</sup> with JCB160 kVA on 5000<sup>\*</sup> hours running



#### Compact in Size

- Easy to load and manoeuvre between sites
- Built-in silencer and best LAT

#### Safe and Sturdy

- Complete body earthing
- External and internal emergency stop button
- Top vent and rain cap
- Designed to work in extreme environment (over  $51^{\circ}$  C)
- Highest block loading capacity (7.2 litre engine)
- Strong and durable doors



# Best-in-class Aesthetics Curved edges Built-in silencer

• Nine stage powder paint finish for both canopy and skid



#### Single Window Product Support

• Product support for entire product range through world-class dealer network



JCB GENERATORS | 4

## JCB POWER PRODUCTS INDIA EXPORTS TO OVER 70+ COUNTRIES!



#### JCB QI CPCB II Compliant Diesel Genset

Genset Model	G63QI	G80QI	GI00QI	G125QI	GI60QI	G180QI	G200QI
Prime Power Rating (kVA/ kWe)	63/50.4	80/64	100/80	125/100	160/128	180/144	200/160
Current Amp at 0.8 pf (lag)	87.5	111.2	139	174	223	250	278
Engine Model	ecoMAX 448TG-60	ecoMAX 448TG-72	ecoMAX 448TAG-92	I 25kVA Mech CPCB II	160kVA Mech CPCB II	180kVA Elec CPCB II	200 kVA Elec CPCB II
kWm / bhp	60 / 82	72 / 98	92 / 125	114.8/156	146.5 / 199	164/223	182/248
No. of Cylinders	4	4	4	6	6	6	6
Displacement/Cubic Capacity (litres)	4.8	4.8	4.8	7.2	7.2	7.2	7.2
Bore x Stroke	106 x 135	106 x 135	106 x 135	105 x137	105 x137	105 ×137	105 x137
Compression Ratio	17.2:1	17.2:1	17.2:1	16.8:1	16.8:1	16.8:1	16.8:1
Cooling	Radiator	Radiator	Radiator	Radiator	Radiator	Radiator	Radiator
Aspiration	Turbocharged	Turbocharged	Turbocharged & Aftercooled				
Governing	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Electronic	Electronic
Lube Oil Sump Capacity (litres)	13.5	13.5	13.5	19.8	19.8	20.2	20.2
Alternator Make	Mecc-alte	Mecc-alte	Mecc-alte	Mecc-alte	Mecc-alte	Mecc-alte	Mecc-alte
Enclosure Protection	IP23	IP23	IP23	IP23	IP23	IP23	IP23
Frequency/rpm	50 Hz/1500 rpm	50 Hz/1500 rpm	50 Hz/1500 rpm	50 Hz/1500 rpm	50 Hz/1500 rpm	50 Hz/1500 rpm	50 Hz/1500 rpm
Insulation	Class H	Class H	Class H	Class H	Class H	Class H	Class H
Voltage Regulation	+/- 1%	+/- 1%	+/- 1%	+/- 1%	+/- 1%	+/- 1%	+/- 1%
Dimensions L x W x H (mm)	2500 x 1230 x 1800	2500 x 1230 x 1800	2500 x 1230 x 1800	3750x1300x1750	3750x1300x1750	4000×1300×2050	4000×1300×2050
Fuel Tank Capacity	180	180	180	310	310	310	310
Dry Weight (kg)	1370	1470	1550	2150	2300	2900	2900



Stay Connected 24x7



Conformance standards: ISO 8528,ISO 3046,BS 5514 & IS 4722

<sup>#</sup>Standard for 180 & 200 kVA only \*T&C Apply.

JCB GENERATORS | 6

#### LiveLink\* with JCB 180-200 kVA Gensets

# THE POWER OF INTELLIGENCE

JCB

G200QI

JCB



Stay Connected 24x7

For the first time in the industry, comes a Genset range of 180-200 kVA, equipped with advanced telematics technology - LiveLink. Empowering you with critical information like fuel theft alerts, service reminders, and hours of operation etc, this range offers you all you need to illuminate your success story.



Dealer's stamp:

JCB INDIA LIMITED 23/7 Mathura Road, Ballabgarh - 121 004 Haryana, India. For more information, call our toll free no. 1800-1037-386 Fax: 91 129 2309050 Website: www.jcb.com



©2009 JCB Sales. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any other means, electronic, mechanical, photocopying or otherwise, without prior permission from JCB Sales. All references in this publication to operating weights, sizes, capacities and other performance measurements are provided for guidance only and may vary dependent upon the exact specification of machine. They should not therefore be relied upon in relation to suitability for a particular application. Guidance and advice should always be sought from your JCB Dealer JCB reserves the right to change specifications without notice. Illustrations and specifications shown may include optional equipment and accessories. The JCB logo is a registered trademark of JC Banford Excavators Ltd.



infinity / November- 202